

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045085 A1

- | | | | | |
|---|-------------------------------|---|---|----|
| (51) International Patent Classification ⁷ : | C22C 38/00 | 10-2004-0070959 | 6 September 2004 (06.09.2004) | KR |
| (21) International Application Number: | | 10-2004-0079664 | 6 October 2004 (06.10.2004) | KR |
| | PCT/KR2004/002901 | 10-2004-0084298 | 21 October 2004 (21.10.2004) | KR |
| (22) International Filing Date: | | (71) Applicant (for all designated States except US): | POSCO | |
| | 10 November 2004 (10.11.2004) | | [KR/KR]; 1 Koedong-dong, Nam-ku, Pohang, Kyung-sang-book-do 790-300 (KR). | |
| (25) Filing Language: | Korean | (72) Inventors; and | | |
| (26) Publication Language: | English | (75) Inventors/Applicants (for US only): | YOON, Jeong-Bong | |
| (30) Priority Data: | | | [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyung-sang-book-do 790-785 (KR). SON, Won-Ho | |
| 10-2003-0079050 | 10 November 2003 (10.11.2003) | | [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyung-sang-book-do 790-785 (KR). KANG, Ki-Bong | |
| 10-2003-0082135 | 19 November 2003 (19.11.2003) | | [KR/KR]; c/o POSCO, 1 Koedong-dong, Nam-ku, Pohang, Kyung-sang-book-do 790-785 (KR). CHO, Noi-Ha | |
| 10-2003-0087566 | 4 December 2003 (04.12.2003) | | [KR/KR]; c/o Kwang-Yang Works, 700 Keumho-dong, Dongkwangyang, Chunlabook-do 545-090 (KR). PARK, Ki-Duck | |
| 10-2003-0087595 | 4 December 2003 (04.12.2003) | | [KR/KR]; c/o Kwang-Yang Works, 700 Keumho-dong, Dongkwangyang, Chunlabook-do 545-090 (KR). | |
| 10-2003-0087534 | 4 December 2003 (04.12.2003) | | (74) Agent: C & S PATENT AND LAW OFFICE; C-2306 Daelim Acrotel, 467-6 Dogok-dong, Kangnam-gu, Seoul 135-971 (KR). | |
| 10-2003-0088134 | 5 December 2003 (05.12.2003) | | (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW. | |
| 10-2003-0088689 | 8 December 2003 (08.12.2003) | | (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, | |
| 10-2003-0088521 | 8 December 2003 (08.12.2003) | | | |
| 10-2003-0088513 | 8 December 2003 (08.12.2003) | | | |
| 10-2003-0094485 | 22 December 2003 (22.12.2003) | | | |
| 10-2003-0099436 | 29 December 2003 (29.12.2003) | | | |
| 10-2003-0099352 | 29 December 2003 (29.12.2003) | | | |
| 10-2004-0041510 | 7 June 2004 (07.06.2004) | | | |
| 10-2004-0041511 | 7 June 2004 (07.06.2004) | | | |
| 10-2004-0041509 | 7 June 2004 (07.06.2004) | | | |
| 10-2004-0066620 | 24 August 2004 (24.08.2004) | | | |
| 10-2004-0070960 | 6 September 2004 (06.09.2004) | | | |

[Continued on next page]

(54) Title: COLD ROLLED STEEL SHEET HAVING AGING RESISTANCE AND SUPERIOR FORMABILITY, AND PROCESS FOR PRODUCING THE SAME

(57) Abstract: A cold rolled steel sheet, and a method of manufacturing the same, designed to have aging resistance and excellent formability suitable for use in automobile bodies, electronic appliances, and the like. The cold rolled steel sheet comprises 0.003 % or less of C, 0.003 ~ 0.03 % of S, 0.01 ~ 0.1 % of Al, 0.02 % or less of N, 0.2 % or less of P, at least one of 0.03 ~ 0.2 % of Mn and 0.005 ~ 0.2 % of Cu, and a balance of Fe and other unavoidable impurities in terms of weight%. When the steel sheet comprises one of Mn and Cu, the composition of Mn, Cu, and S satisfies at least one relationship: $0.58 \cdot \text{Mn}/\text{Sc} + 10 < 1 < 0.5 \cdot \text{Cu}/\text{S} < 10$, and when the steel sheet comprises both Mn and Cu, the composition of Mn, Cu, and S satisfies the relationship: $\text{Mn} + \text{Cu} < 0.3$ and $2 < 0.5 \cdot (\text{Mn} + \text{Cu})/\text{S} < 20$. Participates of MnS, CuS, and (Mn, Cu)S have an average size of 0.2 μm or less. Since carbon content in a solid solution state in a crystal grain is controlled by fine precipitates of MnS, CuS, or (Mn, Cu)S, the steel sheet has enhanced aging resistance and formability, and has excellent yield strength and 15 strength-ductility.



WO 2005/045085 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report